



www.shelfsubsea.com

# "SAT001" 300 metre 12-man Saturation Diving System



## SERVICES REQUIRED

Electric Power - System	:	400 to 480v, 50/60 Hz
Emergency Generator	:	ABS Classed 625 kVA
Compressed Air	:	Not required
Seawater	:	25 gpm
Fresh Water	:	5 gpm

## LIVING CHAMBERS

Chamber 1:	17 m3	:	4 man living
TUP 1:	7.6 m3	:	n/a
Chamber 2:	17 m3	:	6 man living
TUP 2:	7.6 m3	:	n/a
Chamber 3:	15 m3	:	3 man living
HRC:	16.4m3	:	12 Man Emergency

## DIVING BELL

Capacity Men	:	3
Diver Lockout Capability	:	2
Volume	:	4.9 m3
Mating to TUP	:	Side Mating

## RECLAIM SYSTEM

Type	:	Divex Gasmiser
Pumps	:	Electric
Bell Capacity	:	2 Diver Reclaim
Gas Transfer Pumps	:	2 x Corblin

## BUILT :

Year Built	:	2006
Last Upgrade	:	2014
Builder	:	ARC Controls Inc, USA
Class Society	:	ABS
Testing / Certification Standard	:	IMCA D 018 & D024 Rev 2 Built to ABS Class

## HYPERBARIC EVACUATION SYSTEM

Type	:	HRC
Launch System	:	Davit Launch System
Propulsion	:	Tow Only
Capacity Men	:	12 Man
LSP	:	Dedicated w/umbilical

## UMBILICALS

Main Bell	:	330 m
Emergency Bell	:	300 m
Lockout Diver 1	:	45 m
Lockout Diver 2	:	45 m
Bell Man	:	55 m

## LIFESUPPORT MACHINERY

Diver Hot water Unit	:	2 x UNIQUEHydra
CMU Units	:	3 x AC Controls
Scrubbers	:	Divex & Lexmar



Specification subject to change without notice.  
Last revised April 2016

**Shelf Subsea Pty Ltd**  
10 Leeway Court  
OSBORNE PARK WA 6017  
Tel: +61 8 9329 5000  
Fax: +61 8 9329 5002

**Shelf Subsea Pty Ltd**  
Lot 2529 1 Augustus Drive  
KARRATHA WA 6714  
Mobile: 0427 440 108

**Shelf Subsea Pty Ltd**  
16A Wade Court  
SALE VIC 3850  
Tel: +61 3 5143 3233  
Fax: +61 3 5143 2099

**Shelf Subsea Solutions Pte. Ltd**  
23G Loyang Crescent, Loyang  
Offshore Supply Base  
Blk 603 TOPS Ave 6 #01-02,  
Singapore 509023  
Ph +65 8721 6284