



## SLS Mark IV

The Secondary Life Support (SLS) System is an emergency breathing apparatus intended for use by professional saturation divers, operating from a diving bell. The system is intended for use in the event of a fundamental failure of a diver's primary life support system.

The System operates on a semi-closed circuit principle with complete independence from the diver's primary breathing system.

The SLS provides a greater endurance than a standard twin bail-out set which is more commonly used in the industry.

| Depth  | SLS      | Bail-out |
|--------|----------|----------|
| 50msw  | 30 mins  | 17.5mins |
| 100msw | 30 mins  | 9.5mins  |
| 150msw | 28 mins  | 6.6mins  |
| 200msw | 22mins   | 5 mins   |
| 250msw | 19.5mins | 4.0mins  |
| 300msw | 17.5mins | 3.4mins  |



*Specification subject to change without notice. Last revised October 2015*

**Shelf Subsea Pty Ltd**  
 10 Leeway Court  
 OSBORNE PARK WA 6017  
 Tel: +61 8 9329 5000  
 Fax: +61 8 9329 5002

**Shelf Subsea Pty Ltd**  
 Lot 2529 1 Augustus Drive  
 KARRATHA WA 6714  
 Mobile: 0427 440 108

**Shelf Subsea Pty Ltd**  
 16A Wade Court  
 SALE VIC 3850  
 Tel: +61 3 5143 3233  
 Fax: +61 3 5143 2099

**Shelf Subsea Solutions Pte. Ltd**  
 23G Loyang Crescent, Loyang  
 Offshore Supply Base  
 Blk 603 TOPS Ave 6 #01-02,  
 Singapore 509023  
 Mobile: Ph +65 8721 6284