



This multi-purpose deployment a-frame can be easily and quickly mobilized on to a vessel of opportunity due to its design.

A-frame can be supplied with or without winch and/or sheave depending on Project requirements.

It has been utilized for HRC/SPHL recovery and can be supplied with a 25te man-riding winch for this application.

## EQUIPMENT SPECIFICATIONS

### A-Frame

- Max SWL 32te Man riding
- Class Society ABS
- Type Hydraulic Luffing A-Frame
- Footprint 8.1m (W) x 7.6m (L) x 6.4m (H)
- Head Height 5.05m
- Outreach 3.10m

A-frame supplied with twin electrical hydraulic power units for system redundancy.

*Footprint 2.4m (W) x 3.1m (L) x 1.9m (H)*



*Specifications subject to change without notice. Last revised March 2016*



**Shelf Subsea Pty Ltd**  
10 Leeway Court  
OSBORNE PARK WA 6017  
Tel: +61 8 9329 5000  
Fax: +61 8 9329 5002

**Shelf Subsea Pty Ltd**  
Lot 2529 1 Augustus Drive  
KARRATHA WA 6714  
Mobile: 0427 440 108

**Shelf Subsea Pty Ltd**  
16A Wade Court  
SALE VIC 3850  
Tel: +61 3 5143 3233  
Fax: +61 3 5143 2099

**Shelf Subsea Solutions Pte. Ltd**  
23G Loyang Crescent, Loyang  
Offshore Supply Base  
Blk 603 TOPS Ave 6 #01-02,  
Singapore 509023  
Mobile: Ph +65 8721 6284